

# WatchGuard<sup>®</sup> XTM 3 Series

WITH A NEXT-GENERATION XTM 3 SERIES SECURITY SOLUTION, YOUR NETWORK IS:

## RECOMMENDED FOR SMALL TO MIDSIZE BUSINESSES

WatchGuard XTM 3 Series appliances deliver a new class of performance-driven security for growing businesses. The XTM 3 Series offers up to 850 Mbps firewall throughput and security features including full HTTPS inspection, VoIP support, and optional application control.

## WHY BUY AN ALL-IN-ONE SOLUTION?

An all-in-one XTM network security solution integrates complete protection while slashing the time and cost associated with managing multiple single-point security products. All security capabilities work together for a holistic, comprehensive approach to network protection. Your IT staff has more time to focus on other areas of network administration, and your business saves money on support and hardware costs.

**“WatchGuard makes a great firewall and security appliance, and backs it up with tremendous and personal support.”**

*Chet Cromer  
President  
C2IT Consulting, Inc*



## SECURE

- Application-layer content inspection recognizes & blocks threats that stateful packet firewalls cannot detect.
- Wide-ranging proxy protection provides robust security on HTTP, HTTPS, FTP, SMTP, POP3, DNS, TCP/UDP.
- A suite of security subscriptions boosts protection in critical attack areas for complete threat management.
- Optional Application Control keeps unproductive, inappropriate, and dangerous apps off-limits.

## FAST and EFFICIENT

- Up to 850 Mbps firewall throughput and up to 150 Mbps VPN throughput keep data moving.
- Aggregate throughput can reach 70 Mbps, even when security subscriptions are enabled.
- Up to seven 1-Gigabit Ethernet ports support high-speed LAN backbone infrastructures and gigabit WAN connections.
- Interactive, real-time monitoring and reporting – at no additional charge – give an unprecedented view into network security activity so you can take immediate preventive or corrective actions.
- Includes the “Pro” version of the Fireware XTM operating system for advanced networking features, including VLAN support, multi-WAN load balancing, and dynamic routing.
- Intuitive management console centrally manages all security functions.
- Role-based access control (RBAC) allows lead administrators to create custom roles for granular control.
- Drag-and-drop Branch Office VPN setup – three clicks and your remote office is connected.

## FLEXIBLE

- WAN and VPN failover increase performance, redundancy, and reliability.
- Multiple VPN choices (SSL and IPSec) for flexibility in remote access, including support for Apple iOS devices such as the iPhone, iPad, and iPod touch.
- To maximize port utilization, any of the ports can be configured as Internal, External, or Optional.
- Choose the form factor that suits your needs – XTM 330 is rack mount, XTM 33/33-W is tabletop.

## WIRELESS SECURITY

- The XTM 33-W wireless model includes optional dual-band 802.11/n technology for much more responsive wireless network connections and expanded range. Allows users to access 2.4 GHz or less crowded 5GHz band.
- Three distinct security zones give administrators precise control over Internet access privileges for different user groups.
- Wireless guest services segment the Internet for customers/guests.

## PREPARED FOR TOMORROW'S CHALLENGES

- Multi-layered, interlocking security protects the network while throughput remains high. No need to compromise protection for strong performance or vice versa.
- Advanced networking features ensure reliability and the flexibility to meet changing business requirements.
- Secure remote connectivity keeps mobile workforce online and productive.
- Monitoring and reporting tools, included at no extra cost, support industry and regulatory compliance, with drill-down functions that make it easy to pinpoint specific activities.

## XTM 3 SERIES XTM 33 XTM 33-W XTM 330

THROUGHPUT & CONNECTIONS			
Firewall throughput*	850 Mbps	850 Mbps	850 Mbps
VPN throughput*	100 Mbps	100 Mbps	150 Mbps
Aggregate XTM throughput*	45 Mbps	45 Mbps	70 Mbps
Interfaces 10/100/1000	5 copper	5 copper	7 copper
I/O interfaces	1 Serial 1 USB	1 Serial 1 USB	1 Serial 2 USB
Nodes supported (LAN IPs)	Unrestricted	Unrestricted	Unrestricted
Concurrent connections (bi-directional)	40,000	40,000	40,000
VLANs bridging, tagging, routed mode	50	50	50
Local user database	500	500	500
WSM licenses (incl)	4	4	4
Wireless available	-	802.11a/b/g/n	-
VPN TUNNELS			
Branch Office VPN	50	50	50
Mobile VPN IPSec (incl/max)	5/55	5/55	5/55
Mobile VPN SSL	55	55	55
PPTP	50	50	50
SECURITY FEATURES			
Firewall	Stateful packet inspection, deep packet inspection, proxy firewall		
Application proxies	HTTP, HTTPS, SMTP, FTP, DNS, TCP, POP3		
Threat protection	Blocks spyware, DoS attacks, fragmented packets, malformed packets, blended threats, and more		
VoIP	H.323, SIP, call setup and session security		
Security subscriptions	Application Control, Intrusion Prevention, Gateway AV, Reputation Enabled Defense, WebBlocker, spamBlocker		
VPN & AUTHENTICATION			
Encryption	DES, 3DES, AES 128-, 192-, 256-bit		
IPSec	SHA-1, MD5, IKE pre-shared key, 3rd party cert import		
VPN failover	Yes		
SSL	Thin client, Web exchange		
PPTP	Server and Passthrough		
Single sign-on	Transparent Active Directory Authentication		
XAUTH	Radius, LDAP, Secure LDAP, Windows Active Directory		
Other user authentication	VASCO, RSA SecurID, web-based, local, Microsoft Terminal Services and Citrix		
MANAGEMENT			
Management platform	WatchGuard System Manager (WSM) v11 or higher		
Alarms and notifications	SNMP v2/v3, Email, Management System Alert		
Server support	Logging, Reporting, Quarantine, WebBlocker, Management		
Web UI	Supports Windows, Mac, Linux, and Solaris OS		
Command line interface	Includes direct connect and scripting		
STANDARD NETWORKING			
QoS	8 priority queues, DiffServ, modified strict queuing		
IP address assignment	Static, DynDNS, PPPoE, DHCP (server, client, relay)		
CERTIFICATIONS			
Security	ICSA, FIPS 140-2, EAL4+ in progress		
Safety	NRTL/C, CB		
Network	IPv6 Ready Gold (routing)		
Control of hazardous substances	WEEE, RoHS, REACH		



\*Throughput rates will vary based on environment and configuration. Contact your WatchGuard reseller or call WatchGuard directly (1.800.734.9905) for help determining the right model for your network.

## POWERED BY FIREWARE® XTM PRO

XTM 3 Series appliances ship with the Pro version of the Fireware XTM operating system. Advanced networking features<sup>†</sup> include:

NETWORKING FEATURES	FIREWARE XTM PRO
Routing	Static / Dynamic (BGP4, OSPF, RIP v1/v2) Policy-based
NAT	Static, dynamic, 1:1, IPSec traversal
Other Features	High Availability, <sup>†</sup> Port Independence, Multi-WAN failover, Multi-WAN load balancing, Transparent/drop-in mode

<sup>†</sup>High Availability is not currently available on XTM 33 and 33-W. Server load balancing is not available on 3 Series appliances.

## DIMENSIONS AND POWER

### PRODUCT DIMENSIONS

33 Wired	6.1" x 7.5" x 1.25" (15.5 x 19.0 x 3.2 cm)
33 Wireless (antennae up)	7.75" x 10.75" x 5" (19.7 x 27.3 x 12.7 cm)
330	11.25" x 17" x 1.75" (28.6 x 43.2 x 4.5 cm)

### SHIPPING DIMENSIONS

33 Wired or Wireless	10.75" x 13.25" x 3.4" (27.3 x 33.7 x 8.6 cm)
330	18" x 21" x 5.25" (45.7 x 53.3 x 13.3 cm)

### SHIPPING WEIGHT

33 Wired / Wireless	3.2 lbs (1.45 Kg) / 3.6 lbs (1.6 Kg)
330	16.1 lbs (7.3 Kg)

### POWER CONSUMPTION

33 Wired	U.S. 23.33 Watts (80 BTU/hr)
33 Wireless	U.S. 24.0 Watts (82 BTU/hr)
330	U.S. 50 Watts (171 BTU/hr)

### AC POWER

100-240 VAC Autosensing

### RACK MOUNTABLE

1U rack mount kit included with XTM 330 only

## Environment

	OPERATING	STORAGE
TEMPERATURE		
33 Wired or Wireless	32° F to 104° F 0° C to 40° C	-40° F to 158° F -40° C to 70° C
330	32° F to 104° F 0° C to 40° C	-40° F to 158° F -40° C to 70° C
RELATIVE HUMIDITY		
	10% to 85% non-condensing	10% to 95% non-condensing
ALTITUDE		
33 Wired or Wireless	0 to 9,843 ft @ 95° F (3,000 m @ 35° C)	0 to 15,000 ft @ 95° F (4,570 m @ 35° C)
330	0 to 9,843 ft @ 95° F (3,000 m at 35° C)	0 to 15,000 ft @ 95° F (4,570 m at 35° C)
MTBF		
33 Wired or Wireless	129,955 hours @ 104° F (40° C)	
330	51,644 hours @ 77° F (25° C)	

## EXPERT GUIDANCE AND SUPPORT

A subscription to LiveSecurity® Service is included with every XTM 3 appliance for hardware warranty, technical support, and software updates. Renewable in multi-year subscriptions.

## BUY THE BUNDLE AND GET THE WORKS!

Get everything you need for complete threat management at a great price with the Security Bundle. Includes XTM 3 Series appliance and subscriptions to Application Control, Gateway AV, spamBlocker, WebBlocker, Intrusion Prevention Service, Reputation Enabled Defense, and LiveSecurity.\*\* A great deal when you buy together and save!

\*\*XTM 33/33-W Bundle includes standard LiveSecurity with 12/5 tech support. XTM 330 Bundle includes Livesecurity Plus with 24/7 tech support.